

Amendments to the Drawings:

The attached sheets of drawings includes changes to Figures 1-14. These sheets replace original Figures 1-14 in International Application PCT/EP2004/006844. Figures 1-14 have been formalized. In addition, a typographical error appearing in Fig. 9 has been corrected.

Attachment: Replacement Sheets
Annotated Sheet Showing Changes

REMARKS

The above preliminary amendment is made to introduce a substitute specification, to add new claims 10-19, to remove multiple dependencies from claims 3-6 and 9, to amend the abstract page, to introduce formalized drawings, and to correct a typographical error in Figure 9.

A courtesy copy of the present specification is enclosed herewith. However, the World Intellectual Property Office (WIPO) copy should be relied upon if it is already in the U.S. Patent Office.


Applicants respectfully request that the preliminary amendment described herein be entered into the record prior to calculation of the filing fee and prior to examination and consideration of the above-identified application.

If a telephone conference would be helpful in resolving any issues concerning this communication, please contact Applicants' primary attorney-of record, Curtis B. Hamre (Reg. No. 29,165), at (612) 455.3800.

Respectfully submitted,

Hamre, Schumann, Mueller & Larson, P.C.
P.O. Box 2902-902
Minneapolis, Minnesota 55402
(612) 455.3800

Dated: 20 December 2005

By 
Curtis B. Hamre
Reg. No. 29,165

CBH:hjm

SURFACE WATER DRAINAGE SYSTEM

5

RELATED U.S. APPLICATIONS

Not applicable.

10

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

Not applicable.

15

REFERENCE TO MICROFICHE APPENDIX

Not applicable.

20

FIELD OF THE INVENTION

[0001] The invention relates to a surface water drainage system, in particular a drainage channel, ~~according to the precharacterizing clause of Claim 1.~~

25

BACKGROUND OF THE INVENTION

[0002] A surface water drainage system of this kind is known, for example, from
30 the documents CH 681 313 or DE 195 11 788 A1.

[0003] The problems generally encountered with such drainage systems, in particular drainage channels, are associated with the fact that on one hand the cover lying on the structure installed in the ground must be fixed in position so firmly that

even the impulse-like forces encountered when a vehicle travels over the covers cannot release them. On the other hand, the covers must be opened at regular intervals so that cleaning and maintenance work can be done.

5 [0004] In the above-mentioned known surface water drainage systems a latch is attached to the undersurface of the cover, which bridges the cross section of the cover and/or the drainage channel equipped with said latch, and by way of lateral projections locks into undercut areas or recesses provided in the channel body.

10 [0005] The structure of the known systems is relatively elaborate and hence costly.

BRIEF SUMMARY OF THE INVENTION

15

[0006] It is the objective of the invention to ~~develop~~ provide a surface water drainage system of the kind cited at the outset further, in such a way that manufacture and assembly are simplified while still ensuring at least equal durability and reliability of fixation.

20

[0007] ~~This objective is achieved by a surface water drainage system according to Claim 1.~~ According to one aspect of the present invention a surface water drainage system comprises a structure adapted for installation in the ground such that it defines an upper edge and comprising a first locking means; a cover adapted for location on the upper edge of the structure and fabricated from sheet metal having edges forming U-shaped profiles with undercut sections that face toward one another and with a lower side forming a supporting rim; and fixation devices attached to said edges of the cover and comprising second locking means in the form of elastic hook elements that are mounted within said undercut sections and that are adapted for snapping engagement with said first locking means on the structure in order to retain the cover on the structure. According to another aspect of the invention a surface water drainage system comprises a structure adapted for

25

30

installation in the ground such that it defines an upper edge and comprising a first locking means; a cover comprising a cast metal grating adapted for location on the upper edge of the structure and having edges defining recesses; and fixation devices attached to said edges of the cover and comprising second locking means in the
5 form of elastic hook elements that are inserted into said recesses and that are adapted for snapping engagement with said first locking means on the structure in order to retain the cover on the structure.

[0008] The essence ~~It is an essential point~~ of the invention resides in the fact that
10 the locking means associated with the cover are constructed as elastic hook elements and are attached to the edges of the cover. This measure results in a considerable saving of material, because it eliminates regions of the latches provided in the known arrangements that are superfluous with respect to the actual purpose of fixation, being situated in the middle regions of the cover. An additional result is an
15 increase in both durability and fixation performance. That is, whereas in the known systems releasing the snap engagement at one side of the latch or releasing the latch from the grid causes the entire cover no longer to be retained on the structure installed in the ground, in the arrangement according to the invention the locking means on the two sides, i.e. at the edges of the cover, are independent of one
20 another. If one of the locking means is released, the other remains in place unaltered and can continue to perform its fixation function.

[0009] The objective cited above is thus achieved by a surface water drainage system, in particular a drainage channel, comprising a structure that can be installed
25 in the ground, a cover that can be laid onto an upper edge of said structure, and fixation devices that are fixed to the cover. These fixation devices ~~and~~ comprise ~~first~~ locking means in the form of elastic hook elements fixed to the edges of the cover that can be brought into snap-on engagement with other ~~second~~ locking means disposed on the installed structure to hold the cover onto said structure, ~~in that the~~
30 ~~first locking means comprise elastic hook elements fixed to the edges of the cover.~~

[0010] Preferably the ~~first~~ second locking means are detachably fixed to the cover. This makes it possible to exchange these locking means (individually) in case they exhibit material fatigue and/or are damaged in other ways.

5 [0011] Exchanging of the locking means is facilitated by the fact that they are preferably fixed to the cover by a mechanism that does not require use of a tool.

[0012] The ~~first~~ second locking means preferably comprise fixation elements that can be deformed with less force when they ~~the first locking means~~ are being
10 fixed to the cover than when they ~~these first locking means~~ are being removed from the cover. As a result, on one hand easy assembly is ensured (in the factory or during repair work), while on the other hand the fixation elements hold the locking means securely to the cover.

15 [0013] The ~~first~~ second locking means are preferably inserted into undercuts or recesses at the edge of the cover. Thus production of the cover no longer requires the additional expenditure that is otherwise necessary for separate devices with which to attach the locking means.

20 [0014] The ~~first~~ second locking means preferably comprise tensioning devices that brace them ~~the first locking means~~ against the cover so as to ensure that they ~~the latter~~ are fixed in position with no play. As a result, the cover is held to the structure installed in the ground so tightly that it does not rattle.

25 [0015] In a first preferred embodiment the ~~first~~ second locking means are constructed as springs, by bending strips of material. This makes their manufacture relatively inexpensive. In this case the ~~first~~ second locking means are preferably fixed to undercut regions in the cover by means of tabs bent outward from the strip of material. As a result, on one hand easy manufacture with unaltered consumption
30 of material is ensured, while on the other hand the attachment between locking means and cover is extremely durable. Furthermore, in this embodiment the cover is provided in its undercut sections with stamped-out areas or similar offsets, which

can be engaged by the said tabs in order to fix the locking means to the cover. The durability of this arrangement is very high, and the effort of manufacture is low.

5 [0016] In a second preferred embodiment the ~~first~~ second locking means are constructed as elastomer bodies. Such bodies can be easily and economically produced, especially by injection molding, and exhibit great durability, which is very important in particular in view of the aggressive environmental influences (water, road salt, dirt) encountered in this area of application.

10 [0017] ~~Additional characteristics will be apparent from the subordinate claims.~~

[0018] ~~In the following e~~Exemplary embodiments of the invention will now be are described ~~in greater detail~~ with reference to the accompanying drawings, wherein

15

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] Figure 1 shows a first embodiment of the invention, including cover, in
20 front view,

[0020] Figure 2 is a perspective drawing of part of the structure in the direction indicated by the arrow II in Fig. 1,

25 [0021] Figure 3 shows a side view along the line III-III in Fig. 1,

[0022] Figure 4 shows a partial view in the direction of the line IV-IV in Fig. 1,

[0023] Figure 5 shows a side view of a locking device according to another
30 embodiment of the invention,

[0024] Figure 6 shows a cross section through a drainage channel that can be installed in the ground,

[0025] Figure 7 shows a perspective view, from diagonally below, of another
5 embodiment of the invention with a cast-iron grating as cover,

[0026] Figure 8 shows a partial plan view of the arrangement according to Fig.
7,

10 [0027] Figure 9 shows a section along the line IX-IX in Fig. 8,

[0028] Figure 10 shows a perspective view of a locking device according to Fig.
7,

15 [0029] Figure 11 shows a side view of the locking device according to Fig. 10,

[0030] Figure 12 shows a view along the line XII-XII in Fig. 11,

[0031] Figure 13 shows a view along the line XIII-XIII in Fig. 12,

20

[0032] Figure 14 shows a cross section through the cover, as well as locking
element, in a third embodiment, and

[0033] Figure 15 shows an isometric partial view of the exemplary embodiment
25 in Fig. 14.

DETAILED DESCRIPTION OF THE INVENTION

30 [0034] In the following description, the same reference numerals are used for
identical parts and parts with identical actions.

[0035] In the arrangement shown in Figures 1 to 4 the cover 20 has been shaped by bending sheet steel. The edges 21, 22 in this case form undercut sections 23, each of which has a U-shaped profile with a supporting rim 29 on its lower side. The cover 20 is laid into a drainage channel such as is shown in Figure 6, in such a way that the edges 21, 22 are apposed to inner surfaces of lateral folds 14, which are formed by frames 12 that are attached to or poured into the upper edges 11 of a structure 10 that can be installed in the ground. The frames 12 additionally form bearing surfaces 13 on which the cover 20 rests, by way of its supporting rims 29.

[0036] Within the undercut sections 23 hook elements 30 are disposed, to serve as first locking means. In the region where they are situated the contour (in cross section) of the hook elements 30 is identical to the contour of the undercut section, i.e. it is likewise U-shaped, so as to ensure that the hook elements 30 formed from a strip of material make contact over their entire surface.

[0037] Parts of the horizontal (in the assembled state) regions of the hook elements 30 are bent outward to form an upper tab 31 and a lower tab 32, which thus project beyond the otherwise planar upper and lower horizontal surfaces of the hook elements 30. Corresponding to these tabs, stamped-out areas are provided in the edges 21 and 22, specifically on the surface 27 of the cover 20 and in the supporting rims 29, so that in the assembled state the tabs 31, 32, by way of their edges directed toward the interior of the channel, are firmly engaged with the corresponding edges of the stamped-out areas 25, 26. To ensure that this engagement is maintained even if the cover is manufactured with relatively large tolerances, additional tabs are bent outward on the surfaces of the hook elements 30 that face toward the edges 21, 22; these act as tensioning tabs 33. By pressing against the inner (vertical) surfaces of the undercut section 23, these tensioning tabs press the hook elements 30 in the direction towards the interior of the channel.

[0038] Each hook element 30 comprises a nose 34, underneath which there is an insertion slope 35 and above which there is an unlatching slope 36. Thus when a cover 20 with hook elements 30 mounted therein is set onto the structure 10, at first

the insertion slopes 35 slide along the inner edges of the frames 12 and bend the hook elements 30 inward. In the position in which the supporting rims 29 come to rest on the bearing surfaces 13, the noses 34 are caught in notches 50 in the frames, which serve as second locking means. These notches 50 are formed in the frames 12
5 over the entire length of the latter, which enables particularly simple manufacture of the frames.

[0039] The cover 20 is removed by simply pulling it upward, so that the unlatching slopes 36 slide along the inside edges of the frame 12 and bend the hook
10 elements inward again.

[0040] In the embodiment of the hook element 30 shown in Figure 5 the same basic functions are provided as in the embodiment previously described. However, the spring is somewhat slimmer and uses up less material.

15

[0041] In the following another embodiment of the invention is explained with reference to Figures 7 to 13. Here the cover 20 is a cast-iron grating constructed in the conventional way. At the edges of the grating recesses 24 are provided, into which can be inserted the first locking means 30, which in this case are designed as
20 elastomer bodies (in particular, injection-molded). So that these can be fixed within the recesses 24 of the cover 20, the hook elements 30 on both edges are provided with guide slots 37, 38, which engage closely with corresponding guide lugs 28 disposed at the inner edges of the recesses 24. In addition catch elements (not shown) can be provided in order to ensure improved retention of the hook elements
25 30 in the recesses 24.

[0042] The hook elements 30 are dimensioned such that their surfaces 39 are flush with the surface 27 of the cover 20.

30 [0043] The remaining functional components of the hook element 30, namely the nose 34, the insertion slope 35 and the unlatching slope 36, correspond to those in the previously illustrated embodiment of the invention.

[0044] It is of course possible to replace the hook elements formed by bending strips of material, as explained with reference to Figures 1 to 6, by elastomer elements according to Figures 10 to 13. This is illustrated in Figs. 14 and 15 by another exemplary embodiment. Here, again, there is a cover 20 made by bending sheet steel. The edges 21, 22 each have undercut sections 23 with a U-shaped profile, the lower surface of which forms a supporting rim 29. The cover 20 is now, as in the exemplary embodiments previously discussed, laid into a drainage channel according to Fig. 6, with hook elements 30 positioned in the undercut sections 23 to serve as first locking elements. In contrast to the first exemplary embodiment, these hook elements are made of elastomer or a similar flexible material. However, in the region where they are inserted the contour of the hook element 30 is nearly identical to the contour of the undercut section 23, i.e. is likewise U-shaped, so as to ensure that the hook elements 30 make contact over their entire surface.

15

[0045] The hook elements 30 comprise in the horizontal (in the mounted state) region a lower projection 60 that engages a correspondingly shaped recess 26 in the supporting rim 29 of the cover 20. Furthermore, the insertion head 62 of the hook element 30 incorporates a slot 64, which divides the insertion head 62 into a lower insertion head 61 and an upper insertion head 63. In this case the height of the insertion head is somewhat greater than the vertical extent of the undercut section 23 formed in the cover 20. As a result, after the hook element 30 has been put into place, the insertion head 62 is compressed, which is made possible because the slot 64 allows the upper insertion head 63 and the lower insertion head 61 to move towards one another. Because of the elastic construction of the hook element 30, it becomes firmly wedged into the undercut section 23. Even when the cover 20 is subjected to dynamic loads, this arrangement ensures a permanently firm fixation of the hook element 30 within the undercut section 23 of the cover 20. Other advantages of a hook element 30 made of elastomer, of course, are its insensitivity to corrosion and the permanently fixed locking to the drainage channel. It is likewise possible in the case of a cast grating to employ hook elements that are correspondingly shaped by bending strips of material.

30

[0046] List of reference numerals

	10.	Underground structure
5	11.	Upper edge
	12.	Frame
	13.	Bearing surface
	14.	Lateral fold
	20.	Cover
10	21.	Edge
	22.	Edge
	23.	Undercut section
	24.	Recess
	25.	Stamped-out area
15	26.	Stamped-out area
	27.	Surface
	28.	Guide nose
	29.	Supporting rim
	30.	Hook element / 1st <u>2nd</u> locking means
20	31.	Upper tab
	32.	Lower tab
	33.	Tensioning tab
	34.	Nose
	35.	Insertion slope
25	36.	Unlatching slope
	37.	Guide slot
	39.	Surface
	50.	Notch / 2nd <u>1st</u> locking means
	60.	Projection
30	61.	Lower insertion head
	62.	Insertion head
	63.	Upper insertion head

64. Slot